



HIGH EFFICIENCY CRUSHER

PX高效细碎机

设备简介

Introduction

PX高效细碎机引进国外先进技术，经过优化设计和机构改进，而设计制造的第一代高效细碎机。该设备广泛用于化工、建材、冶金、采矿、选煤、制砂及耐火材料等行业，可对石灰石、水泥熟料、铁矿石、页岩、白云岩、花岗岩、石膏、混合材料等中硬度物料进行高效细碎。

PX high-efficiency fine crusher introduces foreign advanced technology, and is designed and manufactured by a new generation of high-efficiency fine crusher after optimization design and mechanism improvement. The equipment is widely used in chemical, building materials, metallurgy, mining, coal preparation, sand making and refractory industries, etc., and can be used in limestone, cement clinker, iron ore, shale, dolomite, granite, gypsum, mixed materials, etc. Hardness materials are efficiently crushed.

产品特点

Features

超高细碎: 新增粒度调节装置，保证出料粒度 ≤3mm占85%;

高效节能: 在同等产量下电机能耗降低40%;

超长寿命: 超高合金组合式锤头，可掉头使用，平均寿命提高4倍;

破碎比大: 可将熟料一、二级，石灰石二、三级破碎，合并为一级破碎;

维修简单: 机器的上壳体可开启，使更换易损件更方便。

Ultra-high fine crushing: new particle size adjustment device to ensure that the discharge granularity ≤ 3mm accounts for 85%;

High efficiency and energy saving: the motor energy consumption is reduced by 40% under the same output;

Long life: Ultra-high alloy combined hammer head, can be used in U-turn, and the average life expectancy is increased by 4 times;

The crushing ratio is large: the first and second grades of clinker and the second and third grades of limestone can be crushed and combined into a first-stage crushing;

Simple maintenance: the upper casing of the machine can be opened, making it easier to replace consumables.

产品参数

Main Specification

型号 Model	最大进料粒度 Max Feeding Size (mm)	平均出料粒度 Average Discharge Granularity (mm)	处理能力 Capacity		功率 Motor Power (kw)	外形尺寸 Overall Dimension (mm)
			水泥熟料 Clinker(t/h)	石灰石 Limestone(t/h)		
PX-8040	80	3	15-20	20-25	37	1395*1506*1390
PX-8080	80	3	25-30	30-40	45	1395*1906*1390
PX-9080	100	3	40-45	45-50	55	1754*1906*1659
PX-9010	100	3	45-50	50-55	55/75	1754*2176*1659
PX-1010	150	3-5	50-60	60-70	90	2138*2590*2021
PX-1210	200	3-5	60-80	70-90	110	2524*2761*2325
PX-1212	200	3-5	60-100	70-110	132	2524*2866*2325
PX-1414	200	5-8	70-150	70-160	200	2550*3120*2670
PX-1616	200	5-8	100-210	110-260	250	2922*3564*2900
PX-1818	200	5-10	120-270	130-310	315	3121*3754*3150

注：规格型号如有变动，恕不另行通知。
Note: Specifications and models are subject to change without notice.